

# Instructions

- 1. Read the IAQ

  Backgrounder and the Background Information for this checklist.
- 2. Keep the
  Background
  Information and
  make a copy of
  this checklist for
  each ventilation
  unit in your school,
  as well as a
  copy for future
  reference.
- 3. Complete the Checklist.
  - Check the "yes,"
     "no," or
     "not applicable"
     box beside each
     item. (A "no"
     response
     requires further
     attention.)
  - Make comments in the "Notes" section as necessary.
- 4. Return the checklist portion of this document to the IAQ Coordinator.

# **Ventilation Checklist**

Name:						
Sc	chool:					
Uı	nit Ventilator/AHU No:					
Room or Area: Date Completed:						
Si	gnature:					
1.	OUTDOOR AIR INTAKES					
1a.	Marked locations of all outdoor air intakes on a small floor plan (for example, a fire escape floor plan)		No	N/A		
1b.	Ensured that the ventilation system was on and operating in "occupied" mode		<u> </u>	_		
AC	CTIVITY 1: OBSTRUCTIONS					
	Ensured that outdoor air intakes are clear of obstructions, debris, clogs, or covers					
1d.	Installed corrective devices as necessary (e.g., if snowdrifts or leaves frequently block an intake)					
AC	CTIVITY 2: POLLUTANT SOURCES					
1e.	Checked ground-level intakes for pollutant sources (dumpsters, loading docks, and bus-idling areas)					
1f.	Checked rooftop intakes for pollutant sources (plumbing vents; kitchen, toilet, or laboratory exhaust fans; puddles; and mist from					
1g.	air-conditioning cooling towers)	<b>_</b>	_	J		
_	intakes (e.g., relocated dumpster or extended exhaust pipe)					
AC	CTIVITY 3: AIRFLOW					
	Obtained chemical smoke (or a small piece of tissue paper or light plastic) Confirmed that outdoor air is entering the intake appropriately					
2.	SYSTEM CLEANLINESS					
	CTIVITY 4: AIR FILTERS					
	Replaced filters per maintenance schedule					
	blowing downstream)					
	Vacuumed filter areas before installing new filters  Confirmed proper fit of filters to prevent air from bypassing (flowing					
	around) the air filter					
	, , , , , , , , , , , , , , , , , , , ,					

# 2. SYSTEM CLEANLINESS (continued)

## **ACTIVITY 5: DRAIN PANS** 2f. Ensured that drain pans slant toward the drain (to prevent water from Yes No N/A 2g. Cleaned drain pans.... **ACTIVITY 6: COILS ACTIVITY 7: AIR-HANDLING UNITS, UNIT VENTILATORS** 2j. Ensured that the interior of air-handling unit(s) or unit ventilator **ACTIVITY 8: MECHANICAL ROOMS** 21. Checked mechanical room for unsanitary conditions, leaks, and spills ........ 2m. Ensured that mechanical rooms and air-mixing chambers are free of trash, chemical products, and supplies ....... 3. CONTROLS FOR OUTDOOR AIR SUPPLY 3a. Ensured that air dampers are at least partially open (minimum position) ......□ 3b. Ensured that minimum position provides adequate outdoor air **ACTIVITY 9: CONTROLS INFORMATION** 3c. Obtained and reviewed all design inside/outside temperature and humidity requirements, controls specifications, as-built mechanical drawings, **ACTIVITY 10: CLOCKS, TIMERS, SWITCHES** 3f. Ensured that settings fit the actual schedule of building use (including **ACTIVITY 11: CONTROL COMPONENTS** 3g. Ensured appropriate system pressure by testing line pressure at both the 3i. Replaced control system filters at the compressor inlet based on the compressor manufacturer's recommendation (for example, when you blow down the tank)...... Set the line pressure at each thermostat and damper actuator at the proper **ACTIVITY 12: OUTDOOR AIR DAMPERS** Ensured that the recirculating relief and/or exhaust dampers are visible 3m. Ensured that air temperature in the indoor area(s) served by each



NOTE: It is necessary to ensure that the damper is operating properly and within the normal range to continue.



3.	CONTROLS FOR OUTDOOR AIR SUPPLY (continued)					
3n.	Checked that the outdoor air damper fully closes within a few minutes of shutting off appropriate air handler	Yes □	No □	N/A		
30.	Checked that the outdoor air damper opens (at least partially with no delay when the air handler is turned on	<sup>'</sup> )				
3p.	If in heating mode, checked that the outdoor air damper goes to its minimum position (without completely closing) when the room thermostat is set to 85°F	🗖				
3q.	If in cooling mode, checked that the outdoor air damper goes to its minimuposition (without completely closing) when the room thermostat is set to 60°F and mixed air thermostat is set to 45°F					
3r.	If the outdoor air damper does not move, confirmed the following items:  • The damper actuator links to the damper shaft, and any linkage set			_		
	• Moving parts are free of impediments (e.g., rust, corrosion)					
	• Electrical wire or pneumatic tubing connects to the damper actuator					
	The outside air thermostat(s) is functioning properly (e.g., in the right location, calibrated correctly)		_	_		
Pro	ceed to Activities 13–16 if the damper seems to be operating properly.	🗷	_	J		
	TIVITY 13: FREEZE STATS					
	Disconnected power to controls (for automatic reset only) to test continuity across terminals					
OR			_	_		
3t.	Confirmed (if applicable) that depressing the manual reset button (usually red) trips the freeze stat (clicking sound indicates freeze stat was			П		
3u.	Assessed the feasibility of replacing all manual reset freeze-stats with automatic reset freeze-stats					
clos	TE: HVAC systems with water coils need protection from the cold. The freezse the outdoor air damper and disconnect the supply air when tripped. The age is $35^{\circ}F$ to $42^{\circ}F$ .					
AC	TIVITY 14: MIXED AIR THERMOSTATS					
3v.	Ensured that the mixed air stat for heating mode is set no higher than 65°F	🗖				
3w.	Ensured that the mixed air stat for cooling mode is set no lower than the room thermostat setting					
AC	TIVITY 15: ECONOMIZERS					
3x.	Confirmed proper economizer settings based on design specifications or local practices	🗅				
NO	TE: The dry-bulb is typically set at 65°F or lower.					
-	Checked that sensor on the economizer is shielded from direct sunlight Ensured that dampers operate properly (for outside air, return air,	🗖				
	exhaust/relief air, and recirculated air), per the design specifications	🗖				
NOTE: Economizers use varying amounts of cool outdoor air to assist with the cooling load of the room or rooms. There are two types of economizers, dry-bulb and enthalpy. Dry-bulb economizers vary the amount of outdoor air based on outdoor temperature, and enthalpy economizers vary the amount of outdoor air based on outdoor temperature.						


and enthalpy economizers vary the amount of outdoor air based on outdoor temperature and humidity level.

# 3. CONTROLS FOR OUTDOOR AIR SUPPLY (continued)

# **ACTIVITY 16: FANS** 3aa. Ensured that all fans (supply fans and associated return or relief fans) that move outside air indoors continuously operate during occupied Yes No N/A NOTE: If fan shuts off when the thermostat is satisfied, adjust control cycle as necessary to ensure sufficient outdoor air supply. 4. AIR DISTRIBUTION **ACTIVITY 17: AIR DISTRIBUTION** 4a. Ensured that supply and return air pathways in the existing ventilation system 4b. Ensured that passive gravity relief ventilation systems and transfer grilles NOTE: If ventilation system is closed or blocked to meet current fire codes, consult with a professional engineer for remedies. 4c. Made sure every occupied space has supply of outdoor air (mechanical NOTE: If outlets have been blocked intentionally to correct drafts or discomfort, investigate and correct the cause of the discomfort and reopen the vents. 4e. Modified the HVAC system to supply outside air to areas without an outdoor air supply ........ 4f. Modified existing HVAC systems to incorporate any room or zone layout 4g. Moved all barriers (for example, room dividers, large free-standing blackboards or displays, bookshelves) that could block movement of 4h. Ensured that unit ventilators are quiet enough to accommodate classroom activities ...... 4i. Ensured that classrooms are free of uncomfortable drafts produced by air **ACTIVITY 18: PRESSURIZATION IN BUILDINGS** NOTE: To prevent infiltration of outdoor pollutants, the ventilation system is designed to maintain positive pressurization in the building. Therefore, ensure that the system, including any exhaust fans, is operating on the "occupied" cycle when doing this activity. 4j. Ensured that air flows out of the building (using chemical smoke) through windows, doors, or other cracks and holes in exterior wall (for example, 5. EXHAUST SYSTEMS **ACTIVITY 19: EXHAUST FAN OPERATION** 5a. Checked (using chemical smoke) that air flows into exhaust fan grille(s) ..... $\Box$ If fans are running but air is not flowing toward the exhaust intake, check for the following: • Inoperable dampers

Obstructed, leaky, or disconnected ductwork Undersized or improperly installed fan

· Broken fan belt





# 5. EXHAUST SYSTEMS (continued)

#### **ACTIVITY 20: EXHAUST AIRFLOW**

NOTE: Prevent migration of indoor contaminants from areas such as bathrooms, kitchens,

## 6. QUANTITY OF OUTDOOR AIR

### **ACTIVITY 22: OUTDOOR AIR MEASUREMENTS AND CALCULATIONS**

NOTE: Refer to "How to Measure Airflow" for techniques.

6c. Divided outdoor air supply (22a) by the number of occupants (22b) to determine the existing quantity of outdoor air supply per person (22c) ....... □

# ACTIVITY 23: ACCEPTABLE LEVELS OF OUTDOOR AIR QUANTITIES

- 6e. Corrected problems with ventilation units that supplied inadequate quantities of outdoor air to ensure that outdoor air quantities (22c) meet the recommended levels in Table 1

## **NOTES**